

#### ZHEJIANG HANGCHA IMP. & EXP. CO., LTD.

Factory site: 666 Xiangfu Road, Hangzhou, Zhejiang, China (311305)

Tel: +86-571-88926735 88926755 Fax: +86-571-88926789 88132890

sales@hcforklift.com www.hcforklift.com



Facebook





YouTube

IS014001:2015





Forklift" App









 $HANGCHA\ GROUP\ CO., LTD.\ reserves\ the\ right\ to\ make\ any\ changes\ without\ notice\ concerning$ colors, equipment, or specifications detailed in this brochure, or to discontinue individual models. The colors of trucks, delivered may differ slightly from those in brochures.

IS09001:2015



## XF Series Diesel / Gasoline / LPG **Counterbalanced Trucks**

with capacities of 4,000 to 5,500kg



#### **HANGCHA** be with you at every stage

Efficient, reliable solutions for your demands

## STAGE V & TIER 4F

With Hangcha you can meet all Stage V/Tier 4f emissions standards which provides customer demands for value, innovation and performance. The technologies include common rail fuel systems, diesel oxidation catalysts (DOC) and diesel particulate filters (DPF). Designed and optimised to every engine model, our forklift truck maximises efficiency and reliability.





Interactive instrument: The instrument adopts 4.0-inch color LCD display with four interactive buttons, and has one CAN bus communication function. The communication protocol is compatible with CANopen and SAE J1939 standards.

#### **HANGCHA Forklift with StageV and T4F**

No.	Capacity	Series	Manufacturer	Engine	Drive power	Model	Emission Std.	Transmission	Power (kw/rpm)
1	4.0-5.5t	XF	KUBOTA	V3307-CR-TIE5B	Diesel	CPCD40/45-XW99BN,CPCD50/55-XXW99BN	Stage V / Tier4 final	OKAMURA	55.4/2200
2	4.0-5.5t	XF	KUBOTA	WG3800-L-E5C	LPG	CPYD40/45-XH11BN,CPYD50/55-XXH11BN	Stage V / EPA Tier 2 / CARB Tier 3	OKAMURA	61.6/2300
3	4.0-5.5t	XF	KUBOTA	WG3800-GL-E3C	GAS/LPG	CPQYD40/45-XH12BN,CPQYD50/55-XXH12BN	Stage V / EPA Tier 2 / CARB Tier 3	OKAMURA	GAS:54.4/2300 LPG:54.6/2300
4	4.0-5.5t	XF	XINCHAI	4E30YG52	Diesel	CPCD40/45-XH8BN,CPCD50/55-XXH8BN	Stage V	OKAMURA	55.8/2200

Note: Stage V applied for European Union also including Israel and Turkey Tier4 Final applied for North American





### **Reliability**

By focusing on enhancing reliability, reducing downtime, the XF series is able to make the greater productivity for customer.

XF series truck just equip with Okamura transmission. Brake drum and hub adopt monolithic construction.



Extra capacity combined radiator with serpentine wave and optimized heat dissipation channel enhance the heat dissipation capability to keep engine reliability even in heavy-duty applications.







XF series features rugged design, stamped frame and engine hood, stamped instrument panel and head guard, heavy profile rail mast combine to provide excellent rigidity, which ensures outstanding reliability even in heavy-duty

Bigger diameter of steering cylinder.

#### **Productivity**

Dynamic load sensing hydraulic steering system, Efficiency lighting system, lower fuel consumption, combine to provide increased productivity and reduced operating costs.



The new Dynamic load sensing hydraulic steering system contributes to reduce loss of hydraulic and improve energy efficiency.



The new efficiency lighting system employs LED illuminant and new type reflector to reduce energy consumption, improve significantly illumination performance and prolong work time.

## **Comfortable Operation**

Optimal visibility in all directions create the best conditions for high productivity through relaxed and safe working.










The extra foot space is provided to reduce operator fatigue significantly. The new wide-open, non-slip step makes getting in and out easy and safe.

The optional Electro-hydraulic proportional control system contributes more sensitive and precise load handling. The easy-to-operate levers provide total load handling operation. An armrest is provided to



In addition to the soft landing system, the soft lifting system is adopted (front lifting cylinders of triplex mast and full free duplex mast), as a result, the noise and shock of the mast significantly decreases.



The developed front lifting cylinders with smaller outer diameter give the operator superior forward

The double front lifting cylinders provide better forward visibility.

In developing the new XF Series, comfort and ease of vibration levels, compound engine damper and full floating power train are adopted. Comfortable operating environments for operator also contribute to increased productivity.







- 1. The new, relocated easy-to-see LCD meter



#### **Safety**

A wide range of technologies are applied to ensure absolute safety for both the operato and those in the surrounding.

An optional rear-pillar assist grip with a horn button enhances safety of operator while traveling in reverse.

The locking device of the engine hood damper and parking brake help add to safety.





- 1. The operator presence sensing system incorporates lifting / tilting and traveling locking function, When the operator leaves the seat, the system automatically locks lifting / tilting and disables traveling to ensure safety.
- **2.** A throttling device is adopted to avoid the mast being out of control even some pipes are broken.

#### **Easy Maintenance**

Careful design facilitates inspection and servicing. Easy maintenance reduces the amount of downtime and helps to reduce cost also.



The new vehicle controller integrates all electrical components, features excellent durability for temperature, water and vibration for most demanding operation.



CUMMINS engine use the special air filter, it can reduce air intake resistance dramatically, equipped with pressure alarm to masterthe maintaining time.





The cover on the Panel can be lifted up simply to check the brake fluid.

The easy-to-operate latch provides quick access to the engine compartment.

The two-piece design makes the floorboard easy to lift and remove for access to the power train.

The fasteners of the radiator cover can be turned easily by hand to enable quick inspections or servicing.

#### **Standards**

Chas	ssiss	Control	Hydraulic
power steering / Anti-	i-slip pedal	/ Power steering	/ Dynamic load sending control valve
eter steering wheel / Rubb	ber pedal	/ Suspension pedal	( Diesel IC )
teering wheel / Engir	ine hood spring	/ Integrated combination switch	/ Hydraulic oil filter
		/ Cable parking brake	/ Tilt cylinder self-lock valve
			/ Hydraulic oil dipstick
			/ Dual pump
)	power steering / Anti- leter steering wheel / Rub	power steering / Anti-slip pedal reter steering wheel / Rubber pedal	r power steering / Anti-slip pedal / Power steering leter steering wheel / Rubber pedal / Suspension pedal steering wheel / Engine hood spring / Integrated combination switch

Truck	Electronics	Electronics		
/ Traction device / Counterweight net / Hand grip / Fan protector / Standard seat / Big capacity aluminum ra / Standard overhead guard / Whirlwind air cleaner / Waterproof cover on the guard / Safety filter / Back view mirror / High-efficient intake mu / Pneumatic tyres / High-efficient exhaust m / Toolbox / Upright exhaust pipe	/ Combination controller / LCD display er / Neutual switch	/ Water temperature gauge / Pre-heat indicator / Charging indicator / Oilpressure warning / Transmission oil pressure warning / Horn / Reversing buzzer	/ Standard wide view duplex mast / Standard forks / Standard fork carriage / Standard load backrest / Mast speed limiting valve / Loading relieve valve / Softlanding system / Side roller	

#### **Options**

Truck	Transmission	Power	Hydraulic	Electronics	Mast
/ Cabin / Cabin heater / Front window / Super elastic tyre / Non-mark tyre(white/green) / Suspension seat / Extinguisher / Cover of tilt cylinder / Heightening overhead guard / Reversing assist grip / Customer painting / OPS(Operator Presence Sensing system) / Boot for tilt cylinder / Additional counterweight	/ Dual driving tyre / Solid tyre	/ DualfuelLPG system / Big capacity copper radiator / Upright exhaust system / Middle-positioned exhaust system / Dual air filter / Net cover of radiator / Sparkle arrester / Purified exhaust system / Swiwel LPG bottle support / Downward LPG bottle support	Auxiliary hydraulic valve     Electro-hydraulic proportional control system     Return oil filter	/ OBD / Front working light / Rear working light / Warning lamp / Speed meter / Over-speed alarm / LED working light	/ Duplex wide view free-lift mast / Triplex wide view free-lift mast / Triplex wide view 4-cylinder free-lift mast / Special forks / Wider fork carriage / Widerload back rest

# Optional Attachments

/ Paper roll clamp	/ Sideshifter
/ Rotating bale clamp	/ Rotating forks
/ Load stabilizer	/ Fork extensioner
/ Multi-drum clamp	/ Load release device
/ Bale clamp	/ Carton clamp
/ Drum clamp	/ Push-pull device
/ Dumping clamp	/ Bucket
/ Crane arm	/ Hook
/ String Pole	/ Lengthened fork











